



**RAY-TECH
INFRARED**

Mini Fusion Xtend



| Dimensions | Standard | Optional |
|--------------------|----------|----------|
| | 115V | 24V |
| Length (Traveling) | 148" | 148" |
| Length (Working) | 175" | 175" |
| Width | 45" | 45" |
| Height | 43" | 54" |
| Chamber Length | 118" | 118" |
| Chamber Width | 15" | 15" |
| Weight (Empty) | 400 LBS | 525 LBS |
| Weight (with Fuel) | 480 LBS | 605 LBS |

| | |
|-------------------------------|---|
| <i>Easy To Maneuver</i> | ✓ |
| <i>Easy To Operate</i> | ✓ |
| <i>Performance Guaranteed</i> | ✓ |

Ideal for joints, cracks or curb work!

The Mini Fusion Xtend features a 118"L x 15"W completely stainless steel infrared heating chamber consisting of three Ray-Tech unique welded ribbon style converters. This walk behind heater is perfect for repairing cracks, heating joints or removing asphalt against buildings or curbs.

| | | | |
|--|------------------------------------|-------------------------------------|-------------------------------|
| Fuel Type | Propane (Vapor) | Blower Type | Standard 115V (Optional: 24V) |
| Fuel Supply | (2) 40 LB Cylinders | # of Blowers | 1 |
| Regulator Setting | 11" Water Column | Chamber Material | Stainless Steel |
| Fuel Tank Connection | Excess Flow Check Connection | Converter Style | Welded Ribbon Orifice |
| Frame Material | 1" x 2" Tube Steel | Converter Material | Stainless Steel |
| Front Wheels | (2) 8" Steel Swivel Casters | # of Converters | (3) 36" Converters |
| Rear Wheels | (2) 10" High Heat Resistant | Grid Style | Stamped & Rolled |
| Power Supply | 115V Generator (Customer Supplied) | Grid Material | High Heat Nickel Alloy |
| Power Connection | Extension Cord (Customer Supplied) | # of Grids | (6) 18" Grids |
| Control Box Material | 14 Gauge Steel | Manifold Material | Stainless Steel |
| Power Supply (For optional 24V configuration) | | (2) 12V batteries & battery charger | |