



**RAY-TECH  
INFRARED**

# 2 Ton Combo



## Dimensions

|                |            |
|----------------|------------|
| Length         | 15' 10"    |
| Width          | 8' 0"      |
| Height         | 8' 5"      |
| Chamber Length | 6'         |
| Chamber Width  | 8'         |
| Weight (Empty) | 6,200 LBS  |
| GVW            | 11,000 LBS |

**Job Size Versatility**



**Easy To Operate**



**Performance Guaranteed**



***Our most popular starter trailer mounted combo!***

The 2 Ton Combo features a 2 ton reclaimer and a 6'L x 8'W completely stainless steel infrared heating chamber consisting of twelve Ray-Tech unique welded ribbon style converters. This trailer mounted combo is ideal for any size jobsites from parking lots and driveways to streets and highways.

|                              |                                |                               |                                        |
|------------------------------|--------------------------------|-------------------------------|----------------------------------------|
| <b>Fuel Type</b>             | Propane (Vapor)                | <b>Blower Type</b>            | (2) 24V Brushless Motors               |
| <b>Fuel Supply</b>           | (1) 60 & (5) 100 LB Cylinders  | <b>Chamber Material</b>       | Stainless Steel                        |
| <b>Regulator Setting</b>     | 11" Water Column               | <b>Converter Style</b>        | Welded Ribbon Orifice                  |
| <b>Frame Material</b>        | 5" Boxed Angle Steel           | <b>Converter Material</b>     | Stainless Steel                        |
| <b>Cross Member Material</b> | 4" Channel Steel               | <b># of Converters</b>        | (6) 30" & (6) 36" Converters           |
| <b>Front Hitch Type</b>      | Steel Pintle Ring              | <b>Grid Style</b>             | Stamped & Rolled                       |
| <b>Front Jack</b>            | Heavy Duty Jack                | <b>Grid Material</b>          | High Heat Nickel Alloy                 |
| <b>Truck Connector Type</b>  | 7 Pole RV Style                | <b># of Grids</b>             | (12) 15" & (12) 18" Grids              |
| <b>Axle</b>                  | (2) 6,000 LB                   | <b>Manifold Material</b>      | Stainless Steel                        |
| <b>Suspension</b>            | Torflex Tandem                 | <b>Power Supply</b>           | (8) 6V Batteries w/ Charger            |
| <b>Brakes</b>                | Electric w/ Breakaway Switch   | <b>Charging Connection</b>    | (1) 115V Outlet for Charging Overnight |
| <b>Trailer Lighting</b>      | LED Directionals, Brakes, etc. | <b>Chamber Lift Operation</b> | (1) Heavy Duty Electric Winch          |
| <b>Reclaimer Capacity</b>    | 2 Tons                         | <b>Discharge Doors</b>        | Manual                                 |
| <b>Top Loading Doors</b>     | Manual                         | <b># of Discharge Doors</b>   | (2) One on Each Side of Reclaimer      |
| <b>Reclaimer Burner Type</b> | Metal Mesh Mat                 | <b># of Reclaimer Burners</b> | (2) 37K Burners                        |